

# Technical data sheet

PH042025

**Roofing tape for Chimney, Wall Abutments,  
Roof Windows and Hatches Waterproofing**

## Material/Application

**Butyl-based aluminum self-adhesive tape used to seal the roof and flashings at chimneys, wall abutments, and other sensitive roof details (roof windows, roof hatches, roof junctions...).**

Onduline® FLASHING BAND has an **excellent gluing performance on various roofing materials and surfaces** (clay/ cement tiles, metal roofs, bitumen sheets, bricks & mortar..) due to its high-quality Butyl base.

The roofing tape has a very good flexibility in all directions and up to 25% stretchability, to fit any angle, thanks to an Innovative technology of transverse and longitudinal pressing. The protective film is in 2 parts, allowing easy application.

Made with UV-stabilized coated aluminum, for high resistance to all weather conditions.

## Technical characteristics

Material	Aluminum, butyl rubber, polyester	
Length (m)	L	2.5 meters
Width (mm)	W	300 mm
Thickness	t	140 µm
Item Net weight	1.45 kg	
Item Net weight/linear meter	0.58 kg/LM [± 0.05 kg/lm]	
Adhesive layer width	290mm	
Protective Film	Silicon, 2 stripes	
Temperature resistance	30°C to +80°C	
Temperature of application	+5°C to +40°C	

## Packaging

Item / box	4
Box dimensions	L : 110 mm W : 110 mm H : 310mm
Items / master box	4

## Handling and storage

**The product should be stored in a dry and covered place, protected against deformations.** Transport it covered, adequately protecting against damage. Protect against frost, make sure to keep it dry. Remove the film protecting the bottom layer directly before installation.

### OFIC Philippines Inc

#73 Bayani Road, Unit 2 Heinen Building, AFPPHOVAI Phase II Western Bicutan, Taguig City Philippines 1630

# ONDULINE FLASHING BAND 300®



## Colors



Black

Grey

Terracotta

Oxide Red

Brown

## Installation

**Onduline® FLASHING BAND is cold applied. No extra tool other than a knife is required. The best application temperature range is above +5 °C.**

1. Surface needs to be well cleaned and dry.
2. Peel off the protective liner, put the tape in the right place, and press it down firmly. Blisters must be avoided.
3. For Chimney or roof window, installation should be started from the bottom, successively on the sides and back on the top. The tape must be about 20 cm longer than the chimney width.
4. In corners, the tape should be joined by "overlapping" or "chopped". If several tapes are applied, overlapping must be at least 50 mm.
5. For perfect and durable waterproofing, fill the connection between the slat and the wall/chimney with a sealing compound (like silicone mastic), topped with a metal "z profile" screwed on the wall.

## Warranty

Onduline grants a warranty for a period of 2 years from the date of purchase. Warranty conditions available upon request.

\* This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters, but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/ distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company but see terms and conditions. .

**Onduline®**  
Lightweight roofing systems