

Technical data sheet

TDS-PH052025

Material/Application

Bitumen material reinforced with cellulosic fibers and thermosetting resin. The composite is colored with inorganic pigments.

Lightweight accessory designed for corrugated roofing sheets.

Product characteristics

Length (m)	L	1000 mm
Width (m)	W	485 mm
Thickness	t	2.9 mm
Heigh of corrugation	H	38 mm
Product surface		0.49 m ²
Weight of product		1.31 kg
Gross Weight per m ²		2.7 kg/m ²

Mechanical & physical properties

Tearing strength	< 200N
Water impermeability	Pass ¹
Proportion of bitumen	> 40%
Homogeneity	Pass ²
Water absorption	< 20%

¹No drop of water underneath sheet after 48 hours

²No area larger than 1cm² without bitumen


Durability

Water impermeability after ageing	Pass ¹
Tearing strength after ageing	< 200 N
Thermal coefficient	< 100.10-6 1/K

Fire resistance

¹ Reaction to fire – EN 13501-1	E
--	---

RIDGE 1000 CLASSIC SR



Colors



Red

Green

Anthracite

Brown

Installation

Special conditions of installation are required. Refer to the installation guide.

Warranty

All the claims will be considered with respect to application recommendations issued by Onduline company but see terms and conditions.



Tariff code - HS: 68079000

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters, but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/ distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company but see terms and conditions. .

OFIC Philippines Inc

#73 Bayani Road, Unit 2 Heinen Building, AFPPHOVAI Phase II Western Bicutan, Taguig City Philippines 1630

Onduline®
Lightweight roofing systems