

Technical data sheet

TDS-PH062025

Material/Application

The CLOSURE CAP is a special type of SLIM CAP which is closed on one side.

It is used to provide a neat finish of the ridge and hip lines, and also prevents birds or other small animals to enter into the roof space.

Made of cellulosic fibers, natural pigments and bitumen. Manufactured using molding process (patented technology).

Full range matching all ONDUVILLA® colours (pigmented/painted).


Product characteristics

Length	L	1055 mm
Width	W	175 mm
Overall height	H	80 mm
Thickness	t	2.2 mm
Gross Weight		0.54 kg
Item surface		.18 m ²

Packaging

Box	20 pcs
Pallet	400 pcs

ONDUVILLA® CLOSURE CAP



Colors

Anthracite Black
Shaded Green

Shaded Red
Shaded Brown

Installation

The CLOSURE CAP is applied using the same method as the SLIM CAP

Warranty

All the claims will be considered with respect to application recommendations issued by Onduline company but see terms and conditions.



Tariff code - HS: 68079000

This TDS was made based on currently available information. Product was made in accordance with above mentioned parameters, but producer/distributor can't anticipate any future change as well as change of regulations. It is the consumer's responsibility to use the product in accordance to producer/ distributor recommendations and his needs. All the claims will be considered with respect to application recommendations issued by Onduline company but see terms and conditions. .

OFIC Philippines Inc

#73 Bayani Road, Unit 2 Heinen Building, AFPPHOVAI Phase II Western Bicutan, Taguig City Philippines 1630

Onduline®
Lightweight roofing systems